









Spec-Kon® lugs

Quick guide



Type	Standard barrel	Long barrel	Wire sizes in mm ²														
			6	10	16	25	35	50	70	95	120	150	185	240	300	400	
One hole	Straight 		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	45 degrees 		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	90 degrees 		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
	Narrow tongue straight 		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
Two holes	Straight 					X	X	X	X	X	X	X	X	X	X	X	X
	Butt splice 		X	X	X	X	X	X	X	X	X	X	X	X	X	X	X

Spec-Kon® Dies selector

Quick guide

Conductor Size [mm ²]	Spec-Kon®		
	Lug Part number	H-CK 240 B-CK 240 T-CK 240	H-CK 400 B-CK 400 T-CK 400
6	6Mx	6TON06M	
10	10Mx	6TON07M	15507M
16	16Mx	6TON075M	155075M
25	25Mx	6TON085M	155085M
35	35Mx	6TON11M	15511M
50	50Mx	6TON12M	15512M
70	70Mx	6TON145M	155145M
95	95Mx	6TON15M	15515M
120	120Mx	6TON18M	15518M
150	150Mx	6TON21M	15521M
185	185Mx	6TON23M	15523M
240	240Mx		15526M
300	300Mx		15529M
400	400Mx		15536M

* For other tools compatibility, please contact your ABB local contact or check our website for your local contact number

<http://new.abb.com/low-voltage/products/connectivity-grounding>