

CONSOLE TYPE: — — —

Number of Zones: _____

- 1 = Single Zone (3.5" x 10" x 8")
- 2 = Dual Zone (3.5" x 12" x 10")
- 3 = Single Zone w/Limit (3.5" x 12" x 10")
- 4 = Dual Zone w/Limit (3.5" x 12" x 10")

Voltage: _____

- A = 120 VAC
- B = 240 VAC

Amperage: _____

- 10 = Up to 10 Amps
- 25 = Up to 25 Amps

Thermocouple Type: _____

- J = Type J Universal - Standard
- K = Type K Universal - Standard
- L = Type J Universal - Mini
- M = Type K Universal - Mini

Communications: _____

- N = None
- C = Communications

Process Control: _____

- N = Non-Profiling/Ramp
- P = Profiling/Ramp

Plug: _____

- 1 = Straight 120 VAC
- 2 = Straight 240 VAC
- 3 = Twist-Lock 120 VAC
- 4 = Twist-Lock 240 VAC

Standard Specifications:

- Control and Power Fusing
- Brushed Aluminum NEMA 1 Enclosure
- Watlow EZ-Zone PM Controller(s) – 1/16 DIN Size, Panel Mount
- Watlow Solid State Relay(s)
- Rubber Feet
- On/Off Switch
- Sub-Panel Mounting for Parts